

PHOTOMETRIC RESULTS

Name:	APL14-DS-27_4000K_2800lm		
Type:	LED PENDANT LIGHT	Diameter:	351 mm
Luminaire:	AL.Die-casting, AL.WIDE EMBOSS REF. (AL.108-55D HJ COATING)	Length:	0 mm
Test no.:	LT-2024-09-06-T02	Width	0 mm
Lamp type:	LED27W, 700mA, 3000K, CRI90	Height:	364 mm
No. of lamps:	1	Power:	27.48 W
Lamp flux:	2996.00 lm	Operator:	ASY
Date:	2024-09-06 PM 3:14:02	LOR:	83.8 %
Comment:	LVED PRO 30W/ 220-240/ 700CS, 25-42VDC, MAX29.4W, 700mA		

**Intensity [cd/klm] APL14-DS-27_4000K_2800lm /
C-Plane measurement**

[illegible]


Intensity [cd/klm] APL14-DS-27_4000K_2800lm / C-Plane measurement

[illegible]

PHOTOMETRIC RESULTS

Name:	APL14-DS-27_4000K_2800lm		
Type:	LED PENDANT LIGHT	Diameter:	351 mm
Luminaire:	AL.Die-casting, AL.WIDE EMBOSS REF. (AL.108-55D HJ COATING)	Length:	0 mm
Test no.:	LT-2024-09-06-T02	Width:	0 mm
Lamp type:	LED27W, 700mA, 3000K, CRI90	Height:	364 mm
No. of lamps:	1	Power:	27.48 W
Lamp flux:	2996.00 lm	Operator:	ASY
Date:	2024-09-06 PM 3:14:02	LOR:	83.8 %
Comment:	LVED PRO 30W/ 220-240/ 700CS, 25-42VDC, MAX29.4W, 700mA		


Polar diagram APL14-DS-27_4000K_2800lm / C-Plane measurement



PHOTOMETRIC RESULTS

Name:	APL14-DS-27_4000K_2800lm		
Type:	LED PENDANT LIGHT	Diameter:	351 mm
Luminaire:	AL.Die-casting, AL.WIDE EMBOSS REF. (AL.108-55D HJ COATING)	Length:	0 mm
Test no.:	LT-2024-09-06-T02	Width:	0 mm
Lamp type:	LED27W, 700mA, 3000K, CRI90	Height:	364 mm
No. of lamps:	1	Power:	27.48 W
Lamp flux:	2996.00 lm	Operator:	ASY
Date:	2024-09-06 PM 3:14:02	LOR:	83.8 %
Comment:	LVED PRO 30W/ 220-240/ 700CS, 25-42VDC, MAX29.4W, 700mA		


Illuminance and Intensity diagram APL14-DS-27_4000K_2800lm / C-Plane measurement



PHOTOMETRIC RESULTS

Name:	APL14-DS-27_4000K_2800lm		
Type:	LED PENDANT LIGHT	Diameter:	351 mm
Luminaire:	AL.Die-casting, AL.WIDE EMBOSS REF. (AL.108-55D HJ COATING)	Length:	0 mm
Test no.:	LT-2024-09-06-T02	Width:	0 mm
Lamp type:	LED27W, 700mA, 3000K, CRI90	Height:	364 mm
No. of lamps:	1	Power:	27.48 W
Lamp flux:	2996.00 lm	Operator:	ASY
Date:	2024-09-06 PM 3:14:02	LOR:	83.8 %
Comment:	LVED PRO 30W/ 220-240/ 700CS, 25-42VDC, MAX29.4W, 700mA		

Isoline diagram APL14-DS-27_4000K_2800lm / C-Plane measurement



Luminaire mounting height above ground: 2.4 m

Luminaire rotation angle: 0 °

PHOTOMETRIC RESULTS

Name:	APL14-DS-27_4000K_2800lm		
Type:	LED PENDANT LIGHT	Diameter:	351 mm
Luminaire:	AL.Die-casting, AL.WIDE EMBOSS REF. (AL.108-55D HJ COATING)	Length:	0 mm
Test no.:	LT-2024-09-06-T02	Width	0 mm
Lamp type:	LED27W, 700mA, 3000K, CRI90	Height:	364 mm
No. of lamps:	1	Power:	27.48 W
Lamp flux:	2996.00 lm	Operator:	ASY
Date:	2024-09-06 PM 3:14:02	LOR:	83.8 %
Comment:	LVED PRO 30W/ 220-240/ 700CS, 25-42VDC, MAX29.4W, 700mA		

LiTG Utilization factors

Ceiling	70	80	80	50	50	80	80	80	50	50	30	0
Wall	50	50	30	50	30	80	50	30	50	30	30	0
Working plane	20	30	30	30	30	10	10	10	10	10	10	0
Roomindices	Utilization coefficients for ceiling mounted luminaires											
0.6	55	57	52	56	52	65	55	51	54	51	51	48
0.8	62	64	59	62	58	71	61	57	60	57	57	53
1	66	68	63	67	62	74	65	61	64	61	60	57
1.25	72	75	70	73	69	78	70	67	69	67	66	63
1.5	75	79	73	75	71	80	73	70	72	69	68	65
2	79	84	79	79	76	83	76	73	75	72	72	69
2.5	81	87	82	82	78	84	78	76	77	74	73	70
3	84	90	85	84	81	85	80	78	78	76	75	72
4	85	92	88	86	83	86	81	79	79	77	76	73
5	87	95	91	87	84	87	83	80	80	78	77	74

Ceiling	70	80	80	50	50	80	80	80	50	50	30	0
Wall	50	50	30	50	30	80	50	30	50	30	30	0
Working plane	20	30	30	30	30	10	10	10	10	10	10	0
Roomindices	Utilization coefficients for pendant mounted luminaires											
0.6	58	60	55	58	53	68	57	53	55	52	51	48
0.8	65	68	62	64	60	73	64	60	61	58	57	53
1	69	73	68	69	65	77	68	64	65	62	61	57
1.25	76	80	75	75	71	81	74	71	71	68	67	63
1.5	78	84	79	78	74	82	76	73	73	71	69	65
2	82	89	85	82	79	84	80	77	76	74	73	69
2.5	85	92	88	84	82	85	82	80	78	76	74	70
3	87	95	92	87	84	86	83	82	80	78	76	72
4	88	98	95	88	86	87	85	83	80	79	77	73
5	90	100	97	89	88	88	86	84	81	80	78	74

PHOTOMETRIC RESULTS

Name:	APL14-DS-27_4000K_2800lm		
Type:	LED PENDANT LIGHT	Diameter:	351 mm
Luminaire:	AL.Die-casting, AL.WIDE EMBOSS REF. (AL.108-55D HJ COATING)	Length:	0 mm
Test no.:	LT-2024-09-06-T02	Width	0 mm
Lamp type:	LED27W, 700mA, 3000K, CRI90	Height:	364 mm
No. of lamps:	1	Power:	27.48 W
Lamp flux:	2996.00 lm	Operator:	ASY
Date:	2024-09-06 PM 3:14:02	LOR:	83.8 %
Comment:	LVED PRO 30W/ 220-240/ 700CS, 25-42VDC, MAX29.4W, 700mA		

UGR Unified Glare Ratios

Ceiling reflectance		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall reflectance		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Floor cavity reflectance		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimension		Viewed crosswise					Viewed endwise				
2H	2H	4.0	5.0	4.3	5.3	5.6	4.0	5.0	4.3	5.3	5.6
2H	3H	4.5	5.4	4.9	5.7	6.0	4.5	5.4	4.9	5.7	6.0
2H	4H	4.6	5.5	5.0	5.8	6.2	4.6	5.5	5.0	5.8	6.2
2H	6H	4.8	5.5	5.2	5.9	6.3	4.8	5.5	5.2	5.9	6.3
2H	8H	4.7	5.5	5.2	5.9	6.3	4.7	5.5	5.2	5.9	6.3
2H	12H	4.7	5.4	5.2	5.8	6.2	4.7	5.4	5.2	5.8	6.2
4H	2H	4.0	4.9	4.4	5.2	5.6	4.0	4.9	4.4	5.2	5.6
4H	3H	4.6	5.3	5.1	5.7	6.1	4.6	5.3	5.1	5.7	6.1
4H	4H	4.9	5.5	5.4	6.0	6.4	4.9	5.5	5.4	6.0	6.4
4H	6H	5.1	5.6	5.5	6.1	6.5	5.1	5.6	5.5	6.1	6.5
4H	8H	5.1	5.6	5.6	6.1	6.5	5.1	5.6	5.6	6.1	6.5
4H	12H	5.1	5.6	5.6	6.0	6.6	5.1	5.6	5.6	6.0	6.6
8H	4H	4.9	5.4	5.4	5.8	6.3	4.9	5.4	5.4	5.8	6.3
8H	6H	5.1	5.5	5.6	6.0	6.5	5.1	5.5	5.6	6.0	6.5
8H	8H	5.2	5.6	5.7	6.1	6.6	5.2	5.6	5.7	6.1	6.6
8H	12H	5.2	5.5	5.8	6.1	6.6	5.2	5.5	5.8	6.1	6.6
12H	4H	4.9	5.3	5.3	5.8	6.3	4.9	5.3	5.3	5.8	6.3
12H	6H	5.1	5.5	5.6	6.0	6.5	5.1	5.5	5.6	6.0	6.5
12H	8H	5.2	5.5	5.7	6.0	6.5	5.2	5.5	5.7	6.0	6.5

PHOTOMETRIC RESULTS

Name:	APL14-DS-27_4000K_2800lm		
Type:	LED PENDANT LIGHT	Diameter:	351 mm
Luminaire:	AL.Die-casting, AL.WIDE EMBOSS REF. (AL.108-55D HJ COATING)	Length:	0 mm
Test no.:	LT-2024-09-06-T02	Width:	0 mm
Lamp type:	LED27W, 700mA, 3000K, CRI90	Height:	364 mm
No. of lamps:	1	Power:	27.48 W
Lamp flux:	2996.00 lm	Operator:	ASY
Date:	2024-09-06 PM 3:14:02	LOR:	83.8 %
Comment:	LVED PRO 30W/ 220-240/ 700CS, 25-42VDC, MAX29.4W, 700mA		

Zonal flux APL14-DS-27_4000K_2800lm / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
0.0	1296.4	1296.4	1296.4	0.93	0.93	0.03	0.03
1.0	1287.1	1287.1	1287.1	7.38	8.31	0.25	0.28
2.0	1263.6	1263.6	1263.6	14.49	22.80	0.48	0.76
3.0	1232.6	1232.6	1232.6	21.19	43.99	0.71	1.47
4.0	1203.2	1203.2	1203.2	27.57	71.57	0.92	2.39
5.0	1175.3	1175.3	1175.3	33.65	105.22	1.12	3.51
6.0	1147.7	1147.7	1147.7	39.41	144.64	1.32	4.83
7.0	1119.5	1119.5	1119.5	44.82	189.46	1.50	6.32
8.0	1089.3	1089.3	1089.3	49.81	239.27	1.66	7.99
9.0	1057.0	1057.0	1057.0	54.32	293.59	1.81	9.80
10.0	1023.4	1023.4	1023.4	58.39	351.98	1.95	11.75
11.0	987.5	987.5	987.5	61.91	413.89	2.07	13.81
12.0	950.6	950.6	950.6	64.94	478.83	2.17	15.98
13.0	915.0	915.0	915.0	67.63	546.45	2.26	18.24
14.0	879.1	879.1	879.1	69.87	616.33	2.33	20.57
15.0	844.4	844.4	844.4	71.80	688.13	2.40	22.97
16.0	811.7	811.7	811.7	73.51	761.63	2.45	25.42
17.0	781.2	781.2	781.2	75.04	836.67	2.50	27.93
18.0	751.1	751.1	751.1	76.26	912.93	2.55	30.47
19.0	722.5	722.5	722.5	77.28	990.21	2.58	33.05
20.0	694.6	694.6	694.6	78.05	1068.26	2.61	35.66
21.0	668.7	668.7	668.7	78.73	1146.98	2.63	38.28
22.0	645.6	645.6	645.6	79.46	1226.44	2.65	40.94
23.0	623.6	623.6	623.6	80.05	1306.50	2.67	43.61
24.0	604.1	604.1	604.1	80.73	1387.22	2.69	46.30
25.0	586.3	586.3	586.3	81.41	1468.63	2.72	49.02
26.0	570.1	570.1	570.1	82.11	1550.74	2.74	51.76
27.0	555.3	555.3	555.3	82.82	1633.56	2.76	54.52
28.0	540.7	540.7	540.7	83.40	1716.96	2.78	57.31
29.0	527.7	527.7	527.7	84.05	1801.02	2.81	60.11

Zonal flux APL14-DS-27_4000K_2800lm / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
30.0	513.1	513.1	513.1	84.29	1885.31	2.81	62.93
31.0	464.0	464.0	464.0	78.52	1963.83	2.62	65.55
32.0	308.1	308.1	308.1	53.64	2017.47	1.79	67.34
33.0	180.4	180.4	180.4	32.27	2049.74	1.08	68.42
34.0	149.7	149.7	149.7	27.50	2077.25	0.92	69.33
35.0	140.3	140.3	140.3	26.44	2103.69	0.88	70.22
36.0	132.1	132.1	132.1	25.51	2129.20	0.85	71.07
37.0	123.6	123.6	123.6	24.43	2153.63	0.82	71.88
38.0	113.9	113.9	113.9	23.05	2176.68	0.77	72.65
39.0	103.3	103.3	103.3	21.37	2198.04	0.71	73.37
40.0	91.6	91.6	91.6	19.35	2217.39	0.65	74.01
41.0	79.3	79.3	79.3	17.09	2234.49	0.57	74.58
42.0	66.5	66.5	66.5	14.61	2249.10	0.49	75.07
43.0	53.7	53.7	53.7	12.04	2261.14	0.40	75.47
44.0	42.6	42.6	42.6	9.72	2270.86	0.32	75.80
45.0	36.4	36.4	36.4	8.44	2279.31	0.28	76.08
46.0	34.6	34.6	34.6	8.17	2287.48	0.27	76.35
47.0	34.1	34.1	34.1	8.19	2295.67	0.27	76.62
48.0	33.6	33.6	33.6	8.20	2303.87	0.27	76.90
49.0	33.1	33.1	33.1	8.20	2312.06	0.27	77.17
50.0	32.5	32.5	32.5	8.19	2320.25	0.27	77.44
51.0	32.0	32.0	32.0	8.17	2328.42	0.27	77.72
52.0	31.5	31.5	31.5	8.15	2336.57	0.27	77.99
53.0	31.0	31.0	31.0	8.12	2344.70	0.27	78.26
54.0	30.3	30.3	30.3	8.06	2352.76	0.27	78.53
55.0	29.7	29.7	29.7	7.99	2360.75	0.27	78.80
56.0	29.1	29.1	29.1	7.91	2368.67	0.26	79.06
57.0	28.3	28.3	28.3	7.81	2376.47	0.26	79.32
58.0	27.7	27.7	27.7	7.71	2384.18	0.26	79.58
59.0	26.9	26.9	26.9	7.58	2391.76	0.25	79.83
60.0	26.1	26.1	26.1	7.44	2399.20	0.25	80.08
61.0	25.3	25.3	25.3	7.28	2406.47	0.24	80.32
62.0	24.5	24.5	24.5	7.10	2413.57	0.24	80.56
63.0	23.6	23.6	23.6	6.90	2420.47	0.23	80.79
64.0	22.6	22.6	22.6	6.68	2427.15	0.22	81.01
65.0	21.7	21.7	21.7	6.45	2433.60	0.22	81.23
66.0	20.6	20.6	20.6	6.19	2439.79	0.21	81.43
67.0	19.6	19.6	19.6	5.93	2445.72	0.20	81.63
68.0	18.5	18.5	18.5	5.65	2451.37	0.19	81.82
69.0	17.5	17.5	17.5	5.36	2456.73	0.18	82.00
70.0	16.5	16.5	16.5	5.08	2461.81	0.17	82.17
71.0	15.5	15.5	15.5	4.80	2466.61	0.16	82.33
72.0	14.5	14.5	14.5	4.52	2471.13	0.15	82.48

Zonal flux APL14-DS-27_4000K_2800lm / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
73.0	13.5	13.5	13.5	4.25	2475.38	0.14	82.62
74.0	12.6	12.6	12.6	3.99	2479.38	0.13	82.76
75.0	11.8	11.8	11.8	3.74	2483.12	0.12	82.88
76.0	10.9	10.9	10.9	3.49	2486.60	0.12	83.00
77.0	10.1	10.1	10.1	3.23	2489.84	0.11	83.11
78.0	9.3	9.3	9.3	2.99	2492.82	0.10	83.21
79.0	8.5	8.5	8.5	2.75	2495.58	0.09	83.30
80.0	7.8	7.8	7.8	2.52	2498.10	0.08	83.38
81.0	7.0	7.0	7.0	2.28	2500.38	0.08	83.46
82.0	6.4	6.4	6.4	2.08	2502.46	0.07	83.53
83.0	5.7	5.7	5.7	1.87	2504.33	0.06	83.59
84.0	5.1	5.1	5.1	1.65	2505.98	0.06	83.64
85.0	4.4	4.4	4.4	1.45	2507.43	0.05	83.69
86.0	3.8	3.8	3.8	1.25	2508.68	0.04	83.73
87.0	3.2	3.2	3.2	1.06	2509.75	0.04	83.77
88.0	2.6	2.6	2.6	0.87	2510.62	0.03	83.80
89.0	1.7	1.7	1.7	0.55	2511.17	0.02	83.82
90.0	0.6	0.6	0.6	0.20	2511.37	0.01	83.82