



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.0V I:0.0550A P:11.70W PF:0.9630 Freq:50.00Hz Lamp Flux:904.343x1 lm		
NAME: ML-CI236	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Mercury Lighting	SUR.:50*50mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 77.29 lm/W			
MODEL		I _{max} (cd)	2207	S/MH (C0/180)	0.59
NOMINAL POWER (W)	11.7	LOR (%)	100.0	S/MH (C90/270)	0.54
RATED VOLTAGE (V)	220	TOTAL FLUX (lm)	904.34	η UP, DN (C0-180)	0.0,50.0
NOMINAL FLUX (lm)	904.343	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0,50.0
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE (V)	220	η down (%)	100.0	CIBSE SHR MAX	0.60



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1680	1706	1714	1706	1680	1706	1714	1706	0- 10	183.2	183.2	20.3,20.3
20	904.2	827.0	780.8	827.0	904.2	827.0	780.8	827.0	10- 20	345.6	528.8	58.5,58.5
30	320.0	260.9	229.3	260.9	320.0	260.9	229.3	260.9	20- 30	229.2	758.0	83.8,83.8
40	89.20	74.09	66.52	74.09	89.20	74.09	66.52	74.09	30- 40	92.68	850.7	94.1,94.1
50	28.74	25.54	23.80	25.54	28.74	25.54	23.80	25.54	40- 50	35.03	885.7	97.9,97.9
60	9.301	8.127	7.654	8.127	9.301	8.127	7.654	8.127	50- 60	14.11	899.8	99.5,99.5
70	2.053	1.136	1.001	1.136	2.053	1.136	1.001	1.136	60- 70	4.083	903.9	100,100
80	0.0297	0.0318	0.0167	0.0318	0.0297	0.0318	0.0167	0.0318	70- 80	0.4074	904.3	100,100
90	0	0	0	0	0	0	0	0	80- 90	0.0174	904.3	100,100
100	0	0	0	0	0	0	0	0	90-100	0	904.3	100,100
110	0	0	0	0	0	0	0	0	100-110	0	904.3	100,100
120	0	0	0	0	0	0	0	0	110-120	0	904.3	100,100
130	0	0	0	0	0	0	0	0	120-130	0	904.3	100,100
140	0	0	0	0	0	0	0	0	130-140	0	904.3	100,100
150	0	0	0	0	0	0	0	0	140-150	0	904.3	100,100
160	0	0	0	0	0	0	0	0	150-160	0	904.3	100,100
170	0	0	0	0	0	0	0	0	160-170	0	904.3	100,100
180	0	0	0	0	0	0	0	0	170-180	0	904.3	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.0V I:0.0550A P:11.70W PF:0.9630 Freq:50.00Hz Lamp Flux:904.343x1 lm		
NAME: ML-CI236	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Mercury Lighting	SUR.:50*50mm	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	61	77
80	68	39
75	695	113
70	2401	1171
65	4507	3105
60	7441	6123
55	11689	9887
50	17883	14808
45	27925	22153


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.0V I:0.0550A P:11.70W PF:0.9630 Freq:50.00Hz Lamp Flux:904.343x1 lm		
NAME: ML-CI236	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Mercury Lighting	SUR.:50*50mm	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.12	1.09	1.07	1.10	1.08	1.06	1.06	1.04	1.03	1.02	1.01	.99	.98	.97	.97	.95
2.0	1.05	1.01	.98	1.03	1.00	.97	1.00	.98	.95	.97	.95	.93	.95	.93	.91	.90
3.0	.99	.95	.91	.98	.94	.91	.95	.92	.89	.93	.90	.88	.91	.88	.86	.85
4.0	.94	.89	.85	.93	.88	.85	.91	.87	.84	.89	.85	.83	.87	.84	.82	.81
5.0	.89	.84	.80	.88	.83	.80	.86	.82	.79	.85	.81	.79	.83	.80	.78	.77
6.0	.85	.80	.76	.84	.79	.76	.83	.78	.75	.81	.77	.75	.80	.77	.74	.73
7.0	.81	.76	.72	.80	.75	.72	.79	.75	.71	.78	.74	.71	.77	.73	.71	.70
8.0	.77	.72	.69	.77	.72	.68	.76	.71	.68	.75	.71	.68	.74	.70	.68	.66
9.0	.74	.69	.65	.74	.69	.65	.73	.68	.65	.72	.68	.65	.71	.67	.65	.64
10.0	.71	.66	.63	.71	.66	.63	.70	.65	.62	.69	.65	.62	.68	.65	.62	.61



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.0V I:0.0550A P:11.70W PF:0.9630 Freq:50.00Hz Lamp Flux:904.343x1 lm		
NAME: ML-CI236	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Mercury Lighting	SUR.:50*50mm	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.160	.091	.029	.153	.087	.028	.141	.081	.026	.129	.075	.024	.119	.069	.022	
2.0	.152	.083	.025	.146	.080	.025	.136	.075	.023	.126	.071	.022	.117	.066	.021	
3.0	.143	.076	.023	.139	.074	.022	.130	.070	.021	.122	.067	.020	.114	.063	.020	
4.0	.136	.071	.021	.132	.069	.020	.124	.066	.020	.117	.063	.019	.111	.060	.018	
5.0	.129	.066	.019	.125	.064	.019	.119	.062	.018	.113	.060	.018	.107	.057	.017	
6.0	.123	.061	.018	.120	.060	.017	.114	.058	.017	.109	.056	.017	.104	.055	.016	
7.0	.117	.058	.016	.114	.057	.016	.109	.055	.016	.105	.054	.016	.100	.052	.015	
8.0	.112	.055	.015	.109	.054	.015	.105	.052	.015	.101	.051	.015	.097	.050	.014	
9.0	.107	.052	.014	.105	.051	.014	.101	.050	.014	.097	.049	.014	.094	.048	.014	
10.0	.103	.049	.014	.101	.049	.014	.097	.048	.013	.094	.047	.013	.091	.046	.013	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.170	.157	.146	.145	.135	.126	.099	.093	.087	.057	.054	.051	.018	.017	.016	
2.0	.154	.133	.115	.132	.114	.099	.090	.079	.069	.052	.046	.041	.017	.015	.013	
3.0	.140	.113	.092	.120	.098	.080	.082	.068	.056	.048	.040	.033	.015	.013	.011	
4.0	.129	.098	.075	.111	.085	.065	.076	.059	.046	.044	.035	.027	.014	.011	.009	
5.0	.119	.087	.062	.103	.075	.054	.071	.052	.038	.041	.031	.023	.013	.010	.007	
6.0	.111	.077	.052	.096	.067	.045	.066	.047	.032	.038	.027	.019	.012	.009	.006	
7.0	.104	.069	.044	.090	.060	.039	.062	.042	.027	.036	.025	.016	.012	.008	.005	
8.0	.098	.063	.038	.085	.054	.033	.059	.038	.024	.034	.023	.014	.011	.007	.005	
9.0	.093	.057	.033	.080	.050	.029	.056	.035	.021	.032	.021	.012	.010	.007	.004	
10.0	.088	.053	.029	.076	.046	.025	.053	.032	.018	.031	.019	.011	.010	.006	.004	

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.0V I:0.0550A P:11.70W PF:0.9630 Freq:50.00Hz Lamp Flux:904.343x1 lm										
NAME: ML-CI236					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:		
MFR.: Mercury Lighting					SUR.:50*50mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	18.1	18.9	18.3	19.1	19.2	16.9	17.7	17.1	17.8	18.0
3H	18.0	18.7	18.2	18.9	19.1	16.7	17.5	17.0	17.7	17.9
4H	17.9	18.6	18.2	18.8	19.1	16.7	17.4	16.9	17.6	17.8
6H	17.8	18.5	18.1	18.7	19.0	16.6	17.2	16.9	17.5	17.7
8H	17.8	18.4	18.1	18.7	18.9	16.5	17.2	16.8	17.4	17.7
12H	17.7	18.4	18.0	18.6	18.9	16.5	17.1	16.8	17.4	17.6
4H 2H	17.9	18.6	18.2	18.9	19.1	16.7	17.4	17.0	17.7	17.9
3H	17.8	18.4	18.1	18.7	19.0	16.6	17.2	16.9	17.5	17.7
4H	17.7	18.3	18.1	18.6	18.9	16.5	17.1	16.8	17.4	17.7
6H	17.6	18.1	18.0	18.4	18.8	16.4	16.9	16.8	17.2	17.6
8H	17.6	18.0	18.0	18.4	18.7	16.3	16.8	16.7	17.2	17.5
12H	17.5	17.9	17.9	18.3	18.7	16.3	16.7	16.7	17.1	17.5
8H 4H	17.6	18.0	18.0	18.4	18.7	16.3	16.8	16.7	17.2	17.5
6H	17.5	17.8	17.9	18.2	18.6	16.2	16.6	16.7	17.0	17.4
8H	17.4	17.7	17.8	18.2	18.6	16.2	16.5	16.6	16.9	17.4
12H	17.3	17.6	17.8	18.1	18.5	16.1	16.4	16.6	16.9	17.3
12H 4H	17.5	17.9	17.9	18.3	18.7	16.3	16.7	16.7	17.1	17.5
6H	17.4	17.7	17.8	18.2	18.6	16.2	16.5	16.6	16.9	17.4
8H	17.3	17.6	17.8	18.1	18.5	16.1	16.4	16.6	16.9	17.3
Variations with the observer position at spacings:										
S = 1.0H	+ 3.0 / - 5.4					+ 2.2 / - 5.2				
1.5H	+ 4.4 / - 4.0					+ 3.3 / - 3.2				
2.0H	+ 4.5 / - 5.6					+ 3.8 / - 5.5				

CIE Pub.117, 904.3 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.3)

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.0V I:0.0550A P:11.70W PF:0.9630 Freq:50.00Hz Lamp Flux:904.343x1 lm		
NAME: ML-CI236	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Mercury Lighting	SUR.:50*50mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) k(RI) x RCR = 5									
k = 0.60	88	81	78	87	81	78	86	81	78	74
0.80	95	89	86	95	89	86	93	89	85	82
1.00	100	94	91	99	94	90	97	93	90	86
1.25	104	98	95	103	98	95	101	97	94	90
1.50	106	102	98	105	101	98	103	99	97	92
2.00	109	105	102	107	104	101	105	102	99	94
2.50	110	107	104	109	106	103	106	103	101	95
3.00	112	109	106	110	107	105	107	105	103	96
4.00	114	111	109	112	110	108	108	107	105	98
5.00	115	113	111	113	111	110	109	108	106	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended				SHRNOM = 1.25			

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.0V I:0.0550A P:11.70W PF:0.9630 Freq:50.00Hz Lamp Flux:904.343x1 lm		
NAME: ML-CI236	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Mercury Lighting	SUR.:50*50mm	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

AAI Figure

Test:U:220.0V I:0.0550A P:11.70W PF:0.9630 Freq:50.00Hz Lamp Flux:904.343x1 lm		
NAME: ML-CI236	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Mercury Lighting	SUR.:50*50mm	Shielding Angle:

Flux out:393.8 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2022-07-15

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:220.0V I:0.0550A P:11.70W PF:0.9630 Freq:50.00Hz Lamp Flux:904.343x1 lm		
NAME: ML-CI236	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Mercury Lighting	SUR.:50*50mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:220.0V I:0.0550A P:11.70W PF:0.9630 Freq:50.00Hz Lamp Flux:904.343x1 lm		
NAME: ML-CI236	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Mercury Lighting	SUR.:50*50mm	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	4507
L_0~180 (75) av	695
L_0~180 (85) av	61
L_90~270 (65) av	3105
L_90~270 (75) av	113
L_90~270 (85) av	77
L_45 (65) av	3419
L_45 (75) av	301
L_45 (85) av	84

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.0V I:0.0550A P:11.70W PF:0.9630 Freq:50.00Hz Lamp Flux:904.343x1 lm		
NAME: ML-CI236	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Mercury Lighting	SUR.:50*50mm	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	45	90	135	180	225	270	315										
0	2077	2164	2207	2164	2077	2164	2207	2164										
5	1967	2040	2074	2040	1967	2040	2074	2040										
10	1680	1706	1714	1706	1680	1706	1714	1706										
15	1298	1262	1238	1262	1298	1262	1238	1262										
20	904	827	781	827	904	827	781	827										
25	566	483	439	483	566	483	439	483										
30	320	261	229	261	320	261	229	261										
35	169	137	120	137	169	137	120	137										
40	89.2	74.1	66.5	74.1	89.2	74.1	66.5	74.1										
45	49.4	42.6	39.2	42.6	49.4	42.6	39.2	42.6										
50	28.7	25.5	23.8	25.5	28.7	25.5	23.8	25.5										
55	16.8	15.1	14.2	15.1	16.8	15.1	14.2	15.1										
60	9.30	8.13	7.65	8.13	9.30	8.13	7.65	8.13										
65	4.76	3.61	3.28	3.61	4.76	3.61	3.28	3.61										
70	2.05	1.14	1.00	1.14	2.05	1.14	1.00	1.14										
75	0.45	0.19	0.07	0.19	0.45	0.19	0.07	0.19										
80	0.03	0.03	0.02	0.03	0.03	0.03	0.02	0.03										
85	0.01	0.02	0.02	0.02	0.01	0.02	0.02	0.02										
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
135	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
145	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
155	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2022-07-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks: