



## DOWNLIGHT




TRIM WITH FLANGE



FLANGELESS TRIM



SQUARE TRIM WITH FLANGE



### MATERIAL

Aluminum Die-Casting, Electrostatic Powder Coating  
ADJUSTABLE RING: PC  
COVER: Clear Glass or Accessories

### STANDARD COLORS

White, Gray, Black

### SOURCE INFORMATION

|                |                         |
|----------------|-------------------------|
| WATTAGE        | 13W / 19W               |
| INPUT VOLTAGE  | 120VAC-277VAC           |
| CRI            | 90                      |
| COLOR TEMP     | 2700K/3000K/3500K/4000K |
| OPERATING TEMP | -4 to +104 °F           |

### ADJUSTABLE ANGLE

Tilt 20°  
Rotation 355°

### TYPE OF LED




COB

### WARRANTY




50 000 hours at 77 °F

### PHOTOMETRICS

#### 13W



#### 19W



Fixture type:

Job information:

## PRODUCT DEFINITION SHEET



|   |   |   |    |    |   |
|---|---|---|----|----|---|
| 1 | 2 | 3 | 4  | 5  | 6 |
| 7 | 8 | 9 | 10 | 11 |   |

| 1                            | 2                            | 3                                      | 4  | 5  | 6  |
|------------------------------|------------------------------|--|--|--|--|
| SERIES                       | WATTAGE                      | LIGHT DISTRIBUTION                     | HOUSING TYPE   | BEAM ANGLE   | LUMEN OUTPUT   |
| <input type="checkbox"/> ARA | <input type="checkbox"/> 13W | <input type="checkbox"/> AD Adjustable | <input type="checkbox"/> TWF Trim With Flange<br><input type="checkbox"/> FLT Flangeless Trim<br><input type="checkbox"/> STWF Square Trim With Flange | <input type="checkbox"/> 16°<br><input type="checkbox"/> 24°<br><input type="checkbox"/> 31° | <input type="checkbox"/> 950 lm<br><input type="checkbox"/> 1350 lm<br><input type="checkbox"/> 1500 lm  |
|                              | <input type="checkbox"/> 19W | <input type="checkbox"/> AD Adjustable | <input type="checkbox"/> STWF Square Trim With Flange  | <input type="checkbox"/> 16°<br><input type="checkbox"/> 24°<br><input type="checkbox"/> 31° | <input type="checkbox"/> 1300 lm<br><input type="checkbox"/> 1800 lm<br><input type="checkbox"/> 2000 lm |

| 7   | 8  | 9  | 10   |
|---|--|--|--|
| FLANGE COLOR  | COLOR TEMP   | MOUNTING                                   | DRIVER   |
| <input type="checkbox"/> W White<br><input type="checkbox"/> G Grey<br><input type="checkbox"/> B Black | 90 CRI<br><input type="checkbox"/> 27K<br><input type="checkbox"/> 30K<br><input type="checkbox"/> 35K<br><input type="checkbox"/> 40K | <input type="checkbox"/> RM Recessed mount | <input type="checkbox"/> V010 0-10V Universal Voltage Remote Driver<br>For other dimming options contact Mercury |

| 11   |
|--|
| VOLTAGE                                      |
| <input type="checkbox"/> UNIV 120VAC-277 VAC |

## CONNECTION



- Inside the ceiling where the lighting fixture is to be installed.
- Connect the driver and luminaires via the quick connect.

