


## DOWNLIGHT



### ADJUSTABLE



### MATERIAL

Aluminum Die-Casting, Electrostatic Powder Coating


### STANDARD COLORS

White, Gray, Black

### SOURCE INFORMATION

WATTAGE	9W
INPUT VOLTAGE	120VAC-277VAC
CRI	90
COLOR TEMP	2700K/3000K/3500K/4000K


### DROP ADJUSTABLE



### ADJUSTABLE ANGLE

Tilt 25°

### WALL WASH




### TYPE OF LED

LED LAMP


### WARRANTY

35 000 hours


### PINHOLE



### PHOTOMETRICS

		h(m)	E(lx)
		1	2331
		2	583
		3	259

### DIRECT



Fixture type:	Job information:
<input type="text"/>	<input type="text"/>

## PRODUCT DEFINITION SHEET



1	2	3	4	5	6
7	8	9	10	11	

1	2	3	4	5
SERIES	WATTAGE	LIGHT DISTRIBUTION	HOUSING TYPE	BEAM ANGLE
<input type="checkbox"/> CLN	<input type="checkbox"/> 9W	<input type="checkbox"/> AD Adjustable <input type="checkbox"/> DAD Drop Adjustable <input type="checkbox"/> WW Wall Wash <input type="checkbox"/> PH Pinhole <input type="checkbox"/> DI Direct	<input type="checkbox"/> TWF Trim With Flange	<input type="checkbox"/> 36°

6	7	8	9
LUMEN OUTPUT	TRIM COLOR	COLOR TEMP	MOUNTING
<input type="checkbox"/> 1200 lm	<input type="checkbox"/> <input type="checkbox"/> W White <input type="checkbox"/> <input type="checkbox"/> G Grey <input type="checkbox"/> <input checked="" type="checkbox"/> B Black	<input checked="" type="checkbox"/> 90 CRI <input type="checkbox"/> 27K <input type="checkbox"/> 30K <input type="checkbox"/> 35K <input type="checkbox"/> 40K	<input type="checkbox"/> RM Recessed Mount

10	11
DRIVER	VOLTAGE
<input type="checkbox"/> V010 0-10V Universal Voltage Remote Driver	<input type="checkbox"/> UNIV 120VAC-277 VAC

For other dimming options contact Mercury

## CONNECTION



- Inside the ceiling where the lighting fixture is to be installed.
- Connect the driver and luminaires via the quick connect.

