

Intensity [cd/klm] CTL-10-CR-330-TFL 4000K / C-Plane measurement

[illegible]


Intensity [cd/klm] CTL-10-CR-330-TFL 4000K / C-Plane measurement

[illegible]

PHOTOMETRIC RESULTS

Name:	CTL-10-CR-330-TFL 4000K		
Type:	LED DOWN LIGHT	Diameter:	30 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS.Ø35	Length:	0 mm
Test no.:	LT-2023-11-29-T05	Width:	0 mm
Lamp type:	LED10W, 700mA, 4000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	10.41 W
Lamp flux:	820.00 lm	Operator:	ASY
Date:	2023-11-29 AM 11:58:35	LOR:	40.8 %
Comment:	EAGL CRISE LS-8-700 SI E1 9.1W Max, 8-13VDC, 700mA		


Polar diagram [cd/klm] CTL-10-CR-330-TFL 4000K / C-Plane measurement



PHOTOMETRIC RESULTS

Name:	CTL-10-CR-330-TFL 4000K		
Type:	LED DOWN LIGHT	Diameter:	30 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS.Ø35	Length:	0 mm
Test no.:	LT-2023-11-29-T05	Width:	0 mm
Lamp type:	LED10W, 700mA, 4000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	10.41 W
Lamp flux:	820.00 lm	Operator:	ASY
Date:	2023-11-29 AM 11:58:35	LOR:	40.8 %
Comment:	EAGL CRISE LS-8-700 SI E1 9.1W Max, 8-13VDC, 700mA		


Illuminance and Intensity diagram CTL-10-CR-330-TFL 4000K / C-Plane measurement



PHOTOMETRIC RESULTS

Name:	CTL-10-CR-330-TFL 4000K		
Type:	LED DOWN LIGHT	Diameter:	30 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS.Ø35	Length:	0 mm
Test no.:	LT-2023-11-29-T05	Width:	0 mm
Lamp type:	LED10W, 700mA, 4000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	10.41 W
Lamp flux:	820.00 lm	Operator:	ASY
Date:	2023-11-29 AM 11:58:35	LOR:	40.8 %
Comment:	EAGL CRISE LS-8-700 SI E1 9.1W Max, 8-13VDC, 700mA		

Ilsoline diagram CTL-10-CR-330-TFL 4000K / C-Plane measurement



Luminaire mounting height above ground: 2.4 m

Luminaire rotation angle: 0 °

PHOTOMETRIC RESULTS

Name:	CTL-10-CR-330-TFL 4000K		
Type:	LED DOWN LIGHT	Diameter:	30 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS.Ø35	Length:	0 mm
Test no.:	LT-2023-11-29-T05	Width:	0 mm
Lamp type:	LED10W, 700mA, 4000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	10.41 W
Lamp flux:	820.00 lm	Operator:	ASY
Date:	2023-11-29 AM 11:58:35	LOR:	40.8 %
Comment:	EAGL CRISE LS-8-700 SI E1 9.1W Max, 8-13VDC, 700mA		

LiTG Utilization factors

Ceiling	70	80	80	50	50	80	80	80	50	50	30	0
Wall	50	50	30	50	30	80	50	30	50	30	30	0
Working plane	20	30	30	30	30	10	10	10	10	10	10	0
Roomindices	Utilization coefficients for ceiling mounted luminaires											
0.6	33	34	32	34	32	36	33	32	33	32	32	30
0.8	36	37	35	36	35	38	35	34	35	34	34	33
1	37	39	37	38	36	39	37	35	36	35	35	34
1.25	40	41	39	40	39	41	39	38	38	37	37	36
1.5	41	43	41	41	40	42	39	39	39	38	38	37
2	42	44	43	42	41	42	41	40	40	39	39	38
2.5	43	46	44	43	42	43	41	40	40	40	39	38
3	43	47	45	44	43	43	42	41	41	40	40	39
4	44	48	46	44	43	43	42	41	41	41	40	39
5	44	49	47	45	44	43	42	42	41	41	40	39

Ceiling	70	80	80	50	50	80	80	80	50	50	30	0
Wall	50	50	30	50	30	80	50	30	50	30	30	0
Working plane	20	30	30	30	30	10	10	10	10	10	10	0
Roomindices	Utilization coefficients for pendant mounted luminaires											
0.6	34	35	33	34	33	37	34	32	33	32	32	30
0.8	37	38	36	37	35	39	36	35	35	34	34	33
1	38	40	38	39	37	40	37	36	37	36	35	34
1.25	41	43	41	41	40	42	39	39	39	38	38	36
1.5	42	44	43	42	41	42	40	39	39	39	38	37
2	43	46	45	43	42	43	41	41	40	40	39	38
2.5	44	47	46	44	43	43	42	41	41	40	40	38
3	44	48	47	45	44	43	42	42	41	41	40	39
4	45	49	48	45	44	43	43	42	41	41	40	39
5	45	50	49	46	45	44	43	43	42	41	40	39

PHOTOMETRIC RESULTS

Name:	CTL-10-CR-330-TFL 4000K		
Type:	LED DOWN LIGHT	Diameter:	30 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS.Ø35	Length:	0 mm
Test no.:	LT-2023-11-29-T05	Width	0 mm
Lamp type:	LED10W, 700mA, 4000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	10.41 W
Lamp flux:	820.00 lm	Operator:	ASY
Date:	2023-11-29 AM 11:58:35	LOR:	40.8 %
Comment:	EAGL CRISE LS-8-700 SI E1 9.1W Max, 8-13VDC, 700mA		

UGR Unified Glare Ratios

Ceiling reflectance		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall reflectance		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Floor cavity reflectance		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimension		Viewed crosswise					Viewed endwise				
2H	2H	10.8	11.6	11.2	11.9	12.3	10.8	11.6	11.2	11.9	12.3
2H	3H	10.8	11.5	11.2	11.9	12.2	10.8	11.5	11.2	11.9	12.2
2H	4H	10.8	11.4	11.2	11.8	12.1	10.8	11.4	11.2	11.8	12.1
2H	6H	10.7	11.3	11.1	11.7	12.1	10.7	11.3	11.1	11.7	12.1
2H	8H	10.6	11.2	11.0	11.6	12.0	10.6	11.2	11.0	11.6	12.0
2H	12H	10.5	11.1	10.9	11.5	11.9	10.5	11.1	10.9	11.5	11.9
4H	2H	10.7	11.4	11.1	11.7	12.1	10.7	11.4	11.1	11.7	12.1
4H	3H	10.7	11.3	11.2	11.7	12.1	10.7	11.3	11.2	11.7	12.1
4H	4H	10.7	11.2	11.1	11.6	12.0	10.7	11.2	11.1	11.6	12.0
4H	6H	10.6	11.0	11.0	11.4	11.9	10.6	11.0	11.0	11.4	11.9
4H	8H	10.5	10.9	11.0	11.4	11.8	10.5	10.9	11.0	11.4	11.8
4H	12H	10.4	10.8	10.9	11.3	11.8	10.4	10.8	10.9	11.3	11.8
8H	4H	10.5	10.9	11.0	11.3	11.8	10.5	10.9	11.0	11.3	11.8
8H	6H	10.4	10.7	10.9	11.2	11.7	10.4	10.7	10.9	11.2	11.7
8H	8H	10.3	10.6	10.9	11.1	11.6	10.3	10.6	10.9	11.1	11.6
8H	12H	10.3	10.5	10.8	11.0	11.5	10.3	10.5	10.8	11.0	11.5
12H	4H	10.4	10.8	10.9	11.2	11.8	10.4	10.8	10.9	11.2	11.8
12H	6H	10.3	10.6	10.9	11.1	11.6	10.3	10.6	10.9	11.1	11.6
12H	8H	10.3	10.5	10.8	11.0	11.5	10.3	10.5	10.8	11.0	11.5

PHOTOMETRIC RESULTS

Name:	CTL-10-CR-330-TFL 4000K		
Type:	LED DOWN LIGHT	Diameter:	30 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS.Ø35	Length:	0 mm
Test no.:	LT-2023-11-29-T05	Width:	0 mm
Lamp type:	LED10W, 700mA, 4000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	10.41 W
Lamp flux:	820.00 lm	Operator:	ASY
Date:	2023-11-29 AM 11:58:35	LOR:	40.8 %
Comment:	EAGL CRISE LS-8-700 SI E1 9.1W Max, 8-13VDC, 700mA		

Zonal flux CTL-10-CR-330-TFL 4000K / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
0.0	1040.4	1040.4	1040.4	0.20	0.20	0.02	0.02
1.0	1038.4	1038.4	1038.4	1.63	1.83	0.20	0.22
2.0	1031.7	1031.7	1031.7	3.24	5.07	0.39	0.62
3.0	1019.7	1019.7	1019.7	4.80	9.87	0.59	1.20
4.0	1002.1	1002.1	1002.1	6.29	16.16	0.77	1.97
5.0	979.1	979.1	979.1	7.67	23.83	0.94	2.91
6.0	951.6	951.6	951.6	8.94	32.77	1.09	4.00
7.0	919.4	919.4	919.4	10.08	42.85	1.23	5.23
8.0	885.0	885.0	885.0	11.08	53.92	1.35	6.58
9.0	849.0	849.0	849.0	11.94	65.87	1.46	8.03
10.0	811.4	811.4	811.4	12.67	78.54	1.55	9.58
11.0	773.4	773.4	773.4	13.27	91.81	1.62	11.20
12.0	735.0	735.0	735.0	13.74	105.55	1.68	12.87
13.0	696.0	696.0	696.0	14.08	119.63	1.72	14.59
14.0	655.6	655.6	655.6	14.26	133.89	1.74	16.33
15.0	613.8	613.8	613.8	14.28	148.18	1.74	18.07
16.0	571.8	571.8	571.8	14.17	162.35	1.73	19.80
17.0	530.1	530.1	530.1	13.94	176.28	1.70	21.50
18.0	488.0	488.0	488.0	13.56	189.84	1.65	23.15
19.0	445.7	445.7	445.7	13.05	202.89	1.59	24.74
20.0	404.2	404.2	404.2	12.43	215.33	1.52	26.26
21.0	364.5	364.5	364.5	11.75	227.07	1.43	27.69
22.0	326.2	326.2	326.2	10.99	238.06	1.34	29.03
23.0	290.4	290.4	290.4	10.20	248.26	1.24	30.28
24.0	257.4	257.4	257.4	9.41	257.68	1.15	31.42
25.0	226.5	226.5	226.5	8.61	266.28	1.05	32.47
26.0	197.7	197.7	197.7	7.79	274.07	0.95	33.42
27.0	170.7	170.7	170.7	6.97	281.04	0.85	34.27
28.0	145.3	145.3	145.3	6.13	287.18	0.75	35.02
29.0	122.5	122.5	122.5	5.34	292.52	0.65	35.67

Zonal flux CTL-10-CR-330-TFL 4000K/ C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
30.0	102.3	102.3	102.3	4.60	297.12	0.56	36.23
31.0	83.4	83.4	83.4	3.86	300.98	0.47	36.70
32.0	66.6	66.6	66.6	3.18	304.16	0.39	37.09
33.0	52.5	52.5	52.5	2.57	306.73	0.31	37.41
34.0	40.9	40.9	40.9	2.06	308.78	0.25	37.66
35.0	31.4	31.4	31.4	1.62	310.40	0.20	37.85
36.0	24.5	24.5	24.5	1.29	311.69	0.16	38.01
37.0	19.7	19.7	19.7	1.06	312.76	0.13	38.14
38.0	16.6	16.6	16.6	0.92	313.68	0.11	38.25
39.0	14.3	14.3	14.3	0.81	314.49	0.10	38.35
40.0	13.3	13.3	13.3	0.77	315.25	0.09	38.45
41.0	12.9	12.9	12.9	0.76	316.01	0.09	38.54
42.0	12.8	12.8	12.8	0.77	316.78	0.09	38.63
43.0	12.9	12.9	12.9	0.79	317.58	0.10	38.73
44.0	12.9	12.9	12.9	0.80	318.38	0.10	38.83
45.0	12.9	12.9	12.9	0.82	319.21	0.10	38.93
46.0	12.8	12.8	12.8	0.83	320.03	0.10	39.03
47.0	12.7	12.7	12.7	0.84	320.87	0.10	39.13
48.0	12.5	12.5	12.5	0.84	321.71	0.10	39.23
49.0	12.1	12.1	12.1	0.82	322.52	0.10	39.33
50.0	11.8	11.8	11.8	0.82	323.34	0.10	39.43
51.0	11.6	11.6	11.6	0.81	324.15	0.10	39.53
52.0	11.0	11.0	11.0	0.78	324.93	0.10	39.63
53.0	10.7	10.7	10.7	0.77	325.70	0.09	39.72
54.0	10.3	10.3	10.3	0.75	326.45	0.09	39.81
55.0	9.7	9.7	9.7	0.72	327.16	0.09	39.90
56.0	9.5	9.5	9.5	0.70	327.87	0.09	39.98
57.0	8.8	8.8	8.8	0.66	328.53	0.08	40.06
58.0	8.2	8.2	8.2	0.63	329.16	0.08	40.14
59.0	7.6	7.6	7.6	0.59	329.74	0.07	40.21
60.0	7.1	7.1	7.1	0.55	330.29	0.07	40.28
61.0	6.5	6.5	6.5	0.51	330.80	0.06	40.34
62.0	5.8	5.8	5.8	0.46	331.26	0.06	40.40
63.0	5.3	5.3	5.3	0.42	331.69	0.05	40.45
64.0	4.5	4.5	4.5	0.37	332.05	0.04	40.49
65.0	4.2	4.2	4.2	0.35	332.40	0.04	40.54
66.0	3.6	3.6	3.6	0.29	332.69	0.04	40.57
67.0	3.2	3.2	3.2	0.26	332.96	0.03	40.60
68.0	3.0	3.0	3.0	0.25	333.20	0.03	40.63
69.0	2.4	2.4	2.4	0.20	333.40	0.02	40.66
70.0	2.1	2.1	2.1	0.18	333.58	0.02	40.68
71.0	2.1	2.1	2.1	0.18	333.76	0.02	40.70
72.0	1.5	1.5	1.5	0.13	333.89	0.02	40.72

Zonal flux CTL-10-CR-330-TFL 4000K / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
73.0	1.2	1.2	1.2	0.10	333.99	0.01	40.73
74.0	1.1	1.1	1.1	0.09	334.08	0.01	40.74
75.0	1.1	1.1	1.1	0.09	334.17	0.01	40.75
76.0	1.1	1.1	1.1	0.09	334.27	0.01	40.76
77.0	1.1	1.1	1.1	0.09	334.36	0.01	40.78
78.0	1.1	1.1	1.1	0.09	334.45	0.01	40.79
79.0	0.9	0.9	0.9	0.08	334.53	0.01	40.80
80.0	0.8	0.8	0.8	0.07	334.61	0.01	40.81
81.0	0.5	0.5	0.5	0.05	334.66	0.01	40.81
82.0	0.5	0.5	0.5	0.05	334.70	0.01	40.82
83.0	0.1	0.1	0.1	0.01	334.71	0.00	40.82
84.0	0.3	0.3	0.3	0.03	334.74	0.00	40.82
85.0	0.2	0.2	0.2	0.02	334.76	0.00	40.82
86.0	0.1	0.1	0.1	0.01	334.77	0.00	40.83
87.0	0.1	0.1	0.1	0.01	334.78	0.00	40.83
88.0	0.0	0.0	0.0	0.00	334.78	0.00	40.83
89.0	0.0	0.0	0.0	0.00	334.78	0.00	40.83
90.0	0.0	0.0	0.0	0.00	334.78	0.00	40.83