

PHOTOMETRIC RESULTS

Name:	CTL-20-CR-1240-TWF 3000K		
Type:	LED DOWN LIGHT	Diameter:	62 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T01	Width	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	100 mm
No. of lamps:	1	Power:	15.39 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 9:50:23	LOR:	70.8 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		

Intensity [cd/klm] CTL-20-CR-1240-TWF 3000K / C-Plane measurement

[illegible]


Intensity [cd/klm] CTL-20-CR-1240-TWF 3000K / C-Plane measurement

[illegible]

PHOTOMETRIC RESULTS

Name:	CTL-20-CR-1240-TWF.L930 BXRH-30G V6 LED15W 3000K 350mA PC.MEDIUM LENS.(32.2D)		
Type:	LED DOWN LIGHT	Diameter:	62 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T01	Width:	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	100 mm
No. of lamps:	1	Power:	15.39 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 9:50:23	LOR:	70.8 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		


Polar diagram CTL-20-CR-1240-TWF 3000K / C-Plane measurement



PHOTOMETRIC RESULTS

Name:	CTL-20-CR-1240-TWF 3000K		
Type:	LED DOWN LIGHT	Diameter:	62 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T01	Width:	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	100 mm
No. of lamps:	1	Power:	15.39 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 9:50:23	LOR:	70.8 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		


Illuminance and Intensity diagram CTL-20-CR-1240-TWF 3000K / C-Plane measurement



PHOTOMETRIC RESULTS

Name:	CTL-20-CR-1240-TWF 3000K		
Type:	LED DOWN LIGHT	Diameter:	62 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T01	Width:	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	100 mm
No. of lamps:	1	Power:	15.39 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 9:50:23	LOR:	70.8 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		

Isoline diagram CTL-20-CR-1240-TWF 3000K / C-Plane measurement



Luminaire mounting height above ground: 2.4 m

Luminaire rotation angle: 0 °

PHOTOMETRIC RESULTS

Name:	CTL-20-CR-1240-TWF 3000K		
Type:	LED DOWN LIGHT	Diameter:	62 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T01	Width:	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	100 mm
No. of lamps:	1	Power:	15.39 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 9:50:23	LOR:	70.8 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		

LiTG Utilization factors

Ceiling	70	80	80	50	50	80	80	80	50	50	30	0
Wall	50	50	30	50	30	80	50	30	50	30	30	0
Working plane	20	30	30	30	30	10	10	10	10	10	10	0
Roomindices	Utilization coefficients for ceiling mounted luminaires											
0.6	60	62	59	61	58	65	59	58	59	57	57	56
0.8	65	66	63	66	63	68	64	62	63	62	61	60
1	67	70	66	68	65	70	66	64	65	64	64	62
1.25	71	74	71	72	70	73	69	68	69	67	67	66
1.5	73	76	73	74	71	74	71	69	70	69	68	67
2	75	79	76	76	73	75	72	71	71	70	70	68
2.5	76	81	78	77	75	75	73	72	72	71	70	69
3	77	83	80	78	76	76	74	73	73	72	71	70
4	78	85	82	79	77	76	74	74	73	72	71	70
5	79	86	84	80	78	76	75	74	73	73	72	70

Ceiling	70	80	80	50	50	80	80	80	50	50	30	0
Wall	50	50	30	50	30	80	50	30	50	30	30	0
Working plane	20	30	30	30	30	10	10	10	10	10	10	0
Roomindices	Utilization coefficients for pendant mounted luminaires											
0.6	61	63	60	62	59	66	60	58	60	58	58	56
0.8	66	69	65	67	64	69	64	62	64	62	62	60
1	69	72	68	69	67	71	67	65	66	64	64	62
1.25	72	76	73	73	71	73	70	69	69	68	67	66
1.5	74	79	76	75	73	74	71	70	70	69	69	67
2	76	82	79	77	75	75	73	72	72	71	70	68
2.5	77	83	81	78	76	76	74	73	72	71	70	69
3	78	85	83	79	78	76	75	74	73	72	71	70
4	79	87	84	80	78	76	75	74	73	73	71	70
5	80	88	86	80	79	76	75	75	73	73	72	70

PHOTOMETRIC RESULTS

Name:	CTL-20-CR-1240-TWF 3000K		
Type:	LED DOWN LIGHT	Diameter:	62 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T01	Width	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	100 mm
No. of lamps:	1	Power:	15.39 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 9:50:23	LOR:	70.8 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		

UGR Unified Glare Ratios

Ceiling reflectance		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall reflectance		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Floor cavity reflectance		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimension		Viewed crosswise					Viewed endwise				
2H	2H	7.5	8.2	7.9	8.6	8.9	7.5	8.2	7.9	8.6	8.9
2H	3H	7.4	8.0	7.8	8.4	8.7	7.4	8.0	7.8	8.4	8.7
2H	4H	7.3	7.9	7.7	8.2	8.6	7.3	7.9	7.7	8.2	8.6
2H	6H	7.2	7.7	7.6	8.1	8.5	7.2	7.7	7.6	8.1	8.5
2H	8H	7.1	7.6	7.5	8.0	8.4	7.1	7.6	7.5	8.0	8.4
2H	12H	7.0	7.5	7.5	7.9	8.3	7.0	7.5	7.5	7.9	8.3
4H	2H	7.2	7.8	7.7	8.2	8.6	7.2	7.8	7.7	8.2	8.6
4H	3H	7.1	7.6	7.5	8.0	8.4	7.1	7.6	7.5	8.0	8.4
4H	4H	7.0	7.4	7.5	7.9	8.3	7.0	7.4	7.5	7.9	8.3
4H	6H	6.9	7.2	7.3	7.7	8.2	6.9	7.2	7.3	7.7	8.2
4H	8H	6.8	7.2	7.3	7.6	8.1	6.8	7.2	7.3	7.6	8.1
4H	12H	6.8	7.1	7.2	7.5	8.1	6.8	7.1	7.2	7.5	8.1
8H	4H	6.8	7.1	7.3	7.6	8.1	6.8	7.1	7.3	7.6	8.1
8H	6H	6.6	6.9	7.1	7.4	7.9	6.6	6.9	7.1	7.4	7.9
8H	8H	6.6	6.9	7.1	7.4	7.9	6.6	6.9	7.1	7.4	7.9
8H	12H	6.6	6.8	7.1	7.3	7.8	6.6	6.8	7.1	7.3	7.8
12H	4H	6.7	7.0	7.2	7.5	8.0	6.7	7.0	7.2	7.5	8.0
12H	6H	6.6	6.8	7.1	7.4	7.9	6.6	6.8	7.1	7.4	7.9
12H	8H	6.5	6.7	7.1	7.3	7.8	6.5	6.7	7.1	7.3	7.8

PHOTOMETRIC RESULTS

Name:	CTL-20-CR-1240-TWF 3000K		
Type:	LED DOWN LIGHT	Diameter:	62 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T01	Width:	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	100 mm
No. of lamps:	1	Power:	15.39 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 9:50:23	LOR:	70.8 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		

Zonal flux CTL-20-CR-1240-TWF 3000K / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
0.0	1927.9	1927.9	1927.9	0.61	0.61	0.05	0.05
1.0	1922.2	1922.2	1922.2	4.83	5.44	0.37	0.41
2.0	1903.0	1903.0	1903.0	9.56	15.00	0.73	1.14
3.0	1871.2	1871.2	1871.2	14.10	29.10	1.07	2.22
4.0	1830.8	1830.8	1830.8	18.39	47.49	1.40	3.62
5.0	1785.0	1785.0	1785.0	22.40	69.89	1.71	5.32
6.0	1737.1	1737.1	1737.1	26.14	96.03	1.99	7.31
7.0	1684.8	1684.8	1684.8	29.56	125.59	2.25	9.57
8.0	1634.2	1634.2	1634.2	32.75	158.34	2.49	12.06
9.0	1582.8	1582.8	1582.8	35.65	193.99	2.72	14.77
10.0	1530.1	1530.1	1530.1	38.26	232.25	2.91	17.69
11.0	1473.8	1473.8	1473.8	40.49	272.74	3.08	20.77
12.0	1413.3	1413.3	1413.3	42.31	315.05	3.22	23.99
13.0	1347.7	1347.7	1347.7	43.65	358.70	3.32	27.32
14.0	1274.9	1274.9	1274.9	44.41	403.11	3.38	30.70
15.0	1194.2	1194.2	1194.2	44.50	447.61	3.39	34.09
16.0	1108.1	1108.1	1108.1	43.98	491.59	3.35	37.44
17.0	1019.2	1019.2	1019.2	42.91	534.49	3.27	40.71
18.0	926.9	926.9	926.9	41.24	575.73	3.14	43.85
19.0	833.2	833.2	833.2	39.06	614.79	2.97	46.82
20.0	739.9	739.9	739.9	36.44	651.23	2.77	49.60
21.0	649.6	649.6	649.6	33.52	684.75	2.55	52.15
22.0	563.4	563.4	563.4	30.39	715.14	2.31	54.47
23.0	483.7	483.7	483.7	27.21	742.35	2.07	56.54
24.0	411.4	411.4	411.4	24.10	766.45	1.84	58.37
25.0	346.5	346.5	346.5	21.08	787.53	1.61	59.98
26.0	291.1	291.1	291.1	18.37	805.90	1.40	61.38
27.0	242.1	242.1	242.1	15.82	821.73	1.21	62.58
28.0	201.2	201.2	201.2	13.60	835.32	1.04	63.62
29.0	167.6	167.6	167.6	11.70	847.02	0.89	64.51
30.0	139.3	139.3	139.3	10.03	857.05	0.76	65.27

Zonal flux CTL-20-CR-1240-TWF 3000K / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
31.0	115.1	115.1	115.1	8.54	865.58	0.65	65.92
32.0	95.4	95.4	95.4	7.28	872.86	0.55	66.48
33.0	79.7	79.7	79.7	6.25	879.11	0.48	66.95
34.0	66.8	66.8	66.8	5.38	884.49	0.41	67.36
35.0	56.1	56.1	56.1	4.63	889.12	0.35	67.72
36.0	46.9	46.9	46.9	3.97	893.09	0.30	68.02
37.0	39.5	39.5	39.5	3.43	896.51	0.26	68.28
38.0	33.3	33.3	33.3	2.95	899.47	0.22	68.50
39.0	28.1	28.1	28.1	2.54	902.01	0.19	68.70
40.0	23.7	23.7	23.7	2.19	904.20	0.17	68.87
41.0	20.2	20.2	20.2	1.91	906.11	0.15	69.01
42.0	17.2	17.2	17.2	1.65	907.76	0.13	69.14
43.0	14.8	14.8	14.8	1.45	909.22	0.11	69.25
44.0	12.8	12.8	12.8	1.28	910.50	0.10	69.34
45.0	11.4	11.4	11.4	1.16	911.65	0.09	69.43
46.0	10.0	10.0	10.0	1.04	912.69	0.08	69.51
47.0	8.9	8.9	8.9	0.94	913.63	0.07	69.58
48.0	8.2	8.2	8.2	0.87	914.50	0.07	69.65
49.0	7.6	7.6	7.6	0.83	915.33	0.06	69.71
50.0	7.2	7.2	7.2	0.79	916.12	0.06	69.77
51.0	6.9	6.9	6.9	0.77	916.89	0.06	69.83
52.0	6.8	6.8	6.8	0.77	917.66	0.06	69.89
53.0	6.6	6.6	6.6	0.76	918.42	0.06	69.95
54.0	6.3	6.3	6.3	0.73	919.15	0.06	70.00
55.0	6.2	6.2	6.2	0.73	919.88	0.06	70.06
56.0	5.9	5.9	5.9	0.71	920.59	0.05	70.11
57.0	5.6	5.6	5.6	0.67	921.26	0.05	70.16
58.0	5.3	5.3	5.3	0.64	921.90	0.05	70.21
59.0	5.0	5.0	5.0	0.62	922.53	0.05	70.26
60.0	4.7	4.7	4.7	0.58	923.11	0.04	70.31
61.0	4.4	4.4	4.4	0.55	923.66	0.04	70.35
62.0	4.1	4.1	4.1	0.53	924.19	0.04	70.39
63.0	3.9	3.9	3.9	0.49	924.68	0.04	70.42
64.0	3.5	3.5	3.5	0.45	925.13	0.03	70.46
65.0	3.2	3.2	3.2	0.42	925.55	0.03	70.49
66.0	2.8	2.8	2.8	0.37	925.93	0.03	70.52
67.0	2.5	2.5	2.5	0.34	926.26	0.03	70.55
68.0	2.1	2.1	2.1	0.27	926.54	0.02	70.57
69.0	1.8	1.8	1.8	0.24	926.78	0.02	70.58
70.0	1.6	1.6	1.6	0.21	926.99	0.02	70.60
71.0	1.4	1.4	1.4	0.19	927.18	0.01	70.62
72.0	1.1	1.1	1.1	0.15	927.34	0.01	70.63
73.0	1.0	1.0	1.0	0.14	927.48	0.01	70.64
74.0	1.0	1.0	1.0	0.14	927.62	0.01	70.65

Zonal flux CTL-20-CR-1240-TWF / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
75.0	0.9	0.9	0.9	0.13	927.74	0.01	70.66
76.0	0.8	0.8	0.8	0.12	927.86	0.01	70.67
77.0	0.8	0.8	0.8	0.11	927.97	0.01	70.68
78.0	0.7	0.7	0.7	0.09	928.06	0.01	70.68
79.0	0.7	0.7	0.7	0.09	928.16	0.01	70.69
80.0	0.7	0.7	0.7	0.09	928.25	0.01	70.70
81.0	0.6	0.6	0.6	0.09	928.34	0.01	70.70
82.0	0.6	0.6	0.6	0.09	928.43	0.01	70.71
83.0	0.6	0.6	0.6	0.09	928.52	0.01	70.72
84.0	0.7	0.7	0.7	0.09	928.61	0.01	70.72
85.0	0.6	0.6	0.6	0.09	928.70	0.01	70.73
86.0	0.6	0.6	0.6	0.09	928.79	0.01	70.74
87.0	0.5	0.5	0.5	0.07	928.86	0.01	70.74
88.0	0.6	0.6	0.6	0.09	928.95	0.01	70.75
89.0	0.7	0.7	0.7	0.09	929.04	0.01	70.76
90.0	0.6	0.6	0.6	0.09	929.13	0.01	70.76