

PHOTOMETRIC RESULTS

Name:	CTL-20-PH-870-TFL 3000K		
Type:	LED DOWN LIGHT	Diameter:	55 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T03	Width	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	15.43 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 10:35:55	LOR:	49.6 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		

Intensity [cd/klm] CTL-20-PH-870-TFL 3000K/ C-Plane measurement

[illegible]


Intensity [cd/klm] CTL-20-PH-870-TFL 3000K / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
75.0	3.9	3.9	3.9	0.55	647.13	0.04	49.29
76.0	3.9	3.9	3.9	0.55	647.68	0.04	49.33
77.0	3.6	3.6	3.6	0.50	648.18	0.04	49.37
78.0	3.3	3.3	3.3	0.46	648.65	0.04	49.40
79.0	3.3	3.3	3.3	0.46	649.11	0.04	49.44
80.0	2.9	2.9	2.9	0.42	649.53	0.03	49.47
81.0	2.7	2.7	2.7	0.38	649.91	0.03	49.50
82.0	2.5	2.5	2.5	0.35	650.26	0.03	49.52
83.0	2.1	2.1	2.1	0.30	650.56	0.02	49.55
84.0	1.9	1.9	1.9	0.27	650.84	0.02	49.57
85.0	1.6	1.6	1.6	0.23	651.07	0.02	49.59
86.0	1.3	1.3	1.3	0.19	651.26	0.01	49.60
87.0	0.9	0.9	0.9	0.13	651.39	0.01	49.61
88.0	0.7	0.7	0.7	0.10	651.48	0.01	49.62
89.0	0.5	0.5	0.5	0.07	651.55	0.01	49.62
90.0	0.4	0.4	0.4	0.05	651.60	0.00	49.63

PHOTOMETRIC RESULTS

Name:	CTL-20-PH-870-TFL 3000K		
Type:	LED DOWN LIGHT	Diameter:	55 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T03	Width:	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	15.43 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 10:35:55	LOR:	49.6 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		


Polar diagram CTL-20-PH-870-TFL 3000K / C-Plane measurement



PHOTOMETRIC RESULTS

Name:	CTL-20-PH-870-TFL 3000K		
Type:	LED DOWN LIGHT	Diameter:	55 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T03	Width:	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	15.43 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 10:35:55	LOR:	49.6 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		


Illuminance and Intensity diagram CTL-20-PH-870-TFL 3000K / C-Plane measurement



PHOTOMETRIC RESULTS

Name:	CTL-20-PH-870-TFL 3000K		
Type:	LED DOWN LIGHT	Diameter:	55 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T03	Width:	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	15.43 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 10:35:55	LOR:	49.6 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		

Isoline diagram CTL-20-PH-870-TFL 3000K / C-Plane measurement



Luminaire mounting height above ground: 2.4 m

Luminaire rotation angle: 0 °

PHOTOMETRIC RESULTS

Name:	CTL-20-PH-870-TFL 3000K		
Type:	LED DOWN LIGHT	Diameter:	62 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T03	Width:	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	15.43 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 10:35:55	LOR:	49.6 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		

LiTG Utilization factors

Ceiling	70	80	80	50	50	80	80	80	50	50	30	0
Wall	50	50	30	50	30	80	50	30	50	30	30	0
Working plane	20	30	30	30	30	10	10	10	10	10	10	0
Roomindices	Utilization coefficients for ceiling mounted luminaires											
0.6	39	40	38	40	38	43	39	37	38	37	37	36
0.8	42	43	41	42	40	45	41	40	41	40	39	38
1	43	45	42	44	42	47	43	41	42	41	41	39
1.25	45	47	45	46	44	48	44	43	44	43	42	41
1.5	47	49	46	47	45	49	45	44	45	43	43	42
2	48	51	48	48	46	50	46	45	45	44	44	42
2.5	49	52	49	49	47	50	47	46	46	45	44	43
3	50	53	51	50	48	51	48	46	46	45	45	43
4	50	55	52	51	49	51	48	47	47	46	45	43
5	51	56	53	51	49	51	49	47	47	46	45	43

Ceiling	70	80	80	50	50	80	80	80	50	50	30	0
Wall	50	50	30	50	30	80	50	30	50	30	30	0
Working plane	20	30	30	30	30	10	10	10	10	10	10	0
Roomindices	Utilization coefficients for pendant mounted luminaires											
0.6	41	42	40	41	39	45	40	39	39	38	38	36
0.8	44	46	43	44	42	47	43	42	42	41	40	38
1	46	48	46	45	44	48	45	43	43	42	41	39
1.25	48	51	48	48	46	49	47	45	45	44	43	41
1.5	49	53	50	49	47	50	48	47	46	45	44	42
2	50	55	53	50	49	51	49	48	46	46	45	42
2.5	51	56	54	51	50	51	49	49	47	46	45	43
3	52	57	55	52	51	51	50	49	47	47	46	43
4	53	59	57	52	51	52	51	50	48	47	46	43
5	53	59	58	53	52	52	51	50	48	48	46	43

PHOTOMETRIC RESULTS

Name:	CTL-20-PH-870-TFL 3000K		
Type:	LED DOWN LIGHT	Diameter:	55 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T03	Width	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	15.43 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 10:35:55	LOR:	49.6 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		

UGR Unified Glare Ratios

Ceiling reflectance		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall reflectance		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Floor cavity reflectance		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimension		Viewed crosswise					Viewed endwise				
2H	2H	8.2	9.0	8.6	9.3	9.6	8.2	9.0	8.6	9.3	9.6
2H	3H	8.7	9.4	9.1	9.8	10.1	8.7	9.4	9.1	9.8	10.1
2H	4H	9.0	9.6	9.4	10.0	10.3	9.0	9.6	9.4	10.0	10.3
2H	6H	9.2	9.8	9.6	10.1	10.5	9.2	9.8	9.6	10.1	10.5
2H	8H	9.2	9.8	9.6	10.1	10.6	9.2	9.8	9.6	10.1	10.6
2H	12H	9.2	9.7	9.6	10.1	10.5	9.2	9.7	9.6	10.1	10.5
4H	2H	8.2	8.9	8.6	9.2	9.6	8.2	8.9	8.6	9.2	9.6
4H	3H	8.9	9.4	9.3	9.8	10.2	8.9	9.4	9.3	9.8	10.2
4H	4H	9.2	9.7	9.7	10.1	10.6	9.2	9.7	9.7	10.1	10.6
4H	6H	9.5	9.9	10.0	10.4	10.8	9.5	9.9	10.0	10.4	10.8
4H	8H	9.6	10.0	10.1	10.4	10.9	9.6	10.0	10.1	10.4	10.9
4H	12H	9.6	10.0	10.1	10.4	11.0	9.6	10.0	10.1	10.4	11.0
8H	4H	9.2	9.6	9.7	10.1	10.5	9.2	9.6	9.7	10.1	10.5
8H	6H	9.5	9.9	10.0	10.4	10.9	9.5	9.9	10.0	10.4	10.9
8H	8H	9.7	10.0	10.3	10.5	11.0	9.7	10.0	10.3	10.5	11.0
8H	12H	9.8	10.0	10.3	10.5	11.1	9.8	10.0	10.3	10.5	11.1
12H	4H	9.2	9.6	9.7	10.0	10.5	9.2	9.6	9.7	10.0	10.5
12H	6H	9.6	9.9	10.1	10.4	10.9	9.6	9.9	10.1	10.4	10.9
12H	8H	9.7	10.0	10.3	10.5	11.0	9.7	10.0	10.3	10.5	11.0

PHOTOMETRIC RESULTS

Name:	CTL-20-PH-870-TFL 3000K		
Type:	LED DOWN LIGHT	Diameter:	55 mm
Luminaire:	AL.Die-casting, PC.MEDIUM LENS. (24D)	Length:	0 mm
Test no.:	LT-2024-11-27-T03	Width:	0 mm
Lamp type:	LED15W, 350mA, 3000K, CRI90	Height:	90 mm
No. of lamps:	1	Power:	15.43 W
Lamp flux:	1313.00 lm	Operator:	ASY
Date:	2024-11-27 AM 10:35:55	LOR:	49.6 %
Comment:	LVED PRO 20W/ 220-240/ 500CS, 25-42VDC, MAX21W, 350mA		

Zonal flux CTL-20-PH-870-TFL 3000K / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
0.0	1892.2	1892.2	1892.2	0.59	0.59	0.05	0.05
1.0	1878.8	1878.8	1878.8	4.72	5.32	0.36	0.40
2.0	1840.7	1840.7	1840.7	9.25	14.57	0.70	1.11
3.0	1780.3	1780.3	1780.3	13.42	27.98	1.02	2.13
4.0	1707.6	1707.6	1707.6	17.15	45.13	1.31	3.44
5.0	1624.7	1624.7	1624.7	20.39	65.52	1.55	4.99
6.0	1537.0	1537.0	1537.0	23.13	88.65	1.76	6.75
7.0	1445.7	1445.7	1445.7	25.37	114.02	1.93	8.68
8.0	1353.6	1353.6	1353.6	27.13	141.15	2.07	10.75
9.0	1262.0	1262.0	1262.0	28.42	169.57	2.16	12.91
10.0	1170.6	1170.6	1170.6	29.27	198.84	2.23	15.14
11.0	1081.0	1081.0	1081.0	29.70	228.54	2.26	17.41
12.0	993.7	993.7	993.7	29.75	258.28	2.27	19.67
13.0	909.0	909.0	909.0	29.44	287.73	2.24	21.91
14.0	825.7	825.7	825.7	28.76	316.49	2.19	24.10
15.0	743.2	743.2	743.2	27.70	344.19	2.11	26.21
16.0	666.8	666.8	666.8	26.46	370.65	2.02	28.23
17.0	594.3	594.3	594.3	25.02	395.67	1.91	30.13
18.0	526.4	526.4	526.4	23.42	419.09	1.78	31.92
19.0	462.7	462.7	462.7	21.69	440.78	1.65	33.57
20.0	403.4	403.4	403.4	19.87	460.64	1.51	35.08
21.0	350.1	350.1	350.1	18.06	478.71	1.38	36.46
22.0	302.6	302.6	302.6	16.32	495.03	1.24	37.70
23.0	259.9	259.9	259.9	14.62	509.65	1.11	38.82
24.0	222.8	222.8	222.8	13.05	522.70	0.99	39.81
25.0	190.2	190.2	190.2	11.57	534.27	0.88	40.69
26.0	162.6	162.6	162.6	10.26	544.53	0.78	41.47
27.0	138.7	138.7	138.7	9.07	553.60	0.69	42.16
28.0	118.7	118.7	118.7	8.03	561.63	0.61	42.77
29.0	102.0	102.0	102.0	7.12	568.75	0.54	43.32
30.0	87.8	87.8	87.8	6.32	575.07	0.48	43.80

Zonal flux CTL-20-PH-870-TFL 3000K / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
31.0	75.4	75.4	75.4	5.59	580.66	0.43	44.22
32.0	65.1	65.1	65.1	4.97	585.63	0.38	44.60
33.0	56.9	56.9	56.9	4.46	590.09	0.34	44.94
34.0	49.9	49.9	49.9	4.02	594.11	0.31	45.25
35.0	43.8	43.8	43.8	3.62	597.73	0.28	45.52
36.0	38.5	38.5	38.5	3.26	600.99	0.25	45.77
37.0	34.1	34.1	34.1	2.95	603.94	0.22	46.00
38.0	30.1	30.1	30.1	2.67	606.61	0.20	46.20
39.0	26.7	26.7	26.7	2.42	609.03	0.18	46.38
40.0	23.8	23.8	23.8	2.20	611.23	0.17	46.55
41.0	21.2	21.2	21.2	2.01	613.23	0.15	46.70
42.0	19.0	19.0	19.0	1.84	615.07	0.14	46.84
43.0	17.3	17.3	17.3	1.70	616.76	0.13	46.97
44.0	15.7	15.7	15.7	1.57	618.33	0.12	47.09
45.0	14.4	14.4	14.4	1.46	619.80	0.11	47.20
46.0	13.3	13.3	13.3	1.38	621.18	0.11	47.31
47.0	12.4	12.4	12.4	1.31	622.48	0.10	47.41
48.0	11.6	11.6	11.6	1.24	623.72	0.09	47.50
49.0	10.9	10.9	10.9	1.19	624.91	0.09	47.59
50.0	10.3	10.3	10.3	1.14	626.05	0.09	47.68
51.0	9.8	9.8	9.8	1.10	627.15	0.08	47.76
52.0	9.3	9.3	9.3	1.05	628.20	0.08	47.84
53.0	9.1	9.1	9.1	1.04	629.24	0.08	47.92
54.0	8.7	8.7	8.7	1.02	630.26	0.08	48.00
55.0	8.4	8.4	8.4	0.99	631.25	0.08	48.08
56.0	8.3	8.3	8.3	0.99	632.23	0.08	48.15
57.0	8.1	8.1	8.1	0.98	633.21	0.07	48.23
58.0	8.0	8.0	8.0	0.98	634.20	0.07	48.30
59.0	7.7	7.7	7.7	0.95	635.14	0.07	48.37
60.0	7.5	7.5	7.5	0.93	636.08	0.07	48.44
61.0	7.2	7.2	7.2	0.91	636.98	0.07	48.51
62.0	6.9	6.9	6.9	0.88	637.86	0.07	48.58
63.0	6.9	6.9	6.9	0.88	638.75	0.07	48.65
64.0	6.5	6.5	6.5	0.84	639.59	0.06	48.71
65.0	6.3	6.3	6.3	0.82	640.41	0.06	48.77
66.0	6.0	6.0	6.0	0.79	641.20	0.06	48.83
67.0	5.7	5.7	5.7	0.76	641.96	0.06	48.89
68.0	5.5	5.5	5.5	0.73	642.70	0.06	48.95
69.0	5.2	5.2	5.2	0.70	643.40	0.05	49.00
70.0	5.2	5.2	5.2	0.70	644.11	0.05	49.06
71.0	4.7	4.7	4.7	0.64	644.75	0.05	49.10
72.0	4.6	4.6	4.6	0.63	645.38	0.05	49.15
73.0	4.6	4.6	4.6	0.63	646.01	0.05	49.20
74.0	4.2	4.2	4.2	0.58	646.59	0.04	49.24

Intensity [cd/klm] CTL-20-PH-870-TFL 3000K / C-Plane measurement

[illegible]