

# LIGHTSTREAMS

## MLD2-M PoE SERIES



Drop or Flat Lens  
Suspended or Surface Mount

### Architectural Linear LED Illuminating System | LIGHTSTREAMS 2



#### Features

- Power over Ethernet (PoE) enabled as Moxlec CoreSync.
- Tunable white feature for standard system or PoE system.
- Extruded aluminum housings for perfectly straight lines of light.
- Narrow profile; 1-7/8-inch width.
- Linear lengths; 2-ft. and above in increments of one-inch.
- Featured lens is a 1/2-inch drop style.
- Optional: 1-inch or 1-1/2 inch drop lens.
- Optional: flat lens style.
- Custom formulated high diffusion extruded acrylic lens.
- Non-glare matte-white polyester powder coating finish.
- Cable or stem mount from ceiling, or direct surface mount.
- Cataloged standard or custom set lumens-per-foot performances.
- 80 CRI standard. 90 CRI available.
- Fixture lumens per watt ratios up to 110.
- Standard and custom corners.
- American Made.



#### Performance

Based on 4ft. Module, 3500K, 80 CRI



Lumens per Foot	Delivered Lumens (L)	System Watts (W)	Lumens per Watt (LPW)
<b>A05 LENS</b>			
400	1600	16.0	100
500	2000	20.3	99
625	2500	25.9	97
825	3300	35.4	93
950	3800	41.6	91
<b>A10 LENS</b>			
400	1600	15.3	105
500	2000	19.3	104
625	2500	24.6	102
825	3300	33.5	99
990	3960	41.3	96
<b>A15 LENS</b>			
400	1600	14.6	110
500	2000	18.3	109
625	2500	23.3	107
825	3300	31.8	104
1040	4160	41.5	100

Multiplier for other Color Temp (K)

3000K	97%
3500K	100%
4000K	102%
5000K	103%



Actual performance may differ by +/- 5% when operating between 12V-42VDC.



Fixture Type:

Job Information:



# MLD2-M PoE Series | LIGHTSTREAMS 2

Architectural Linear LED Illuminating System | Drop or Flat Lens | Suspended or Surface Mount

Ex. MLD2-M-144-825-35K-40VDC-A05-180996



Options

MLD2		40VDC							Options	
SERIES	MOUNTING	MODULE OR ROW LENGTH	LUMENS/ FT	COLOR TEMP	LED MODULES FORWARD VOLTAGE	DIFFUSER	MOLEX DRIVER	EMERGENCY LIGHTING	MISC.	
MLD2 LightStreams 2	<b>M</b> Suspended Cable Mount  <b>M1</b> Surface Mount  <b>M2</b> Suspended Stem Mount	<b>48</b> 48" Length  <b>96</b> 96" Length  <b>144</b> 144" Length  Custom or Row Length, 24" and above in 1" increments.  Ex. in inches 82, 384, etc.	<b>A05 LENS</b> 400 500 625 825 950  <b>A10 LENS</b> 400 500 625 825 990  <b>A15 LENS</b> 400 500 625 825 1040  Custom Lumen Packages.	<b>30K</b> <b>35K</b> <b>40K</b> <b>50K</b> Upon Request  <b>TW</b> 27K-57K  <b>927K</b> <b>930K</b> <b>935K</b> <b>940K</b>	40VDC	<b>A05</b> 1/2" Drop  <b>A10</b> 1" Drop  <b>A15</b> 1-1/2" Drop  <b>ASO</b> Flat	<b>Single Channel</b> 180996-XXXX-250-300mA 180996-XXXX-300-350mA 180996-XXXX-360-500mA 180996-XXXX-510-700mA 180996-XXXX-710-880mA 180996-XXXX-890-1050mA  <b>Dual Channel</b> 180996-XXXX-300-350mA 180996-XXXX-360-500mA 180996-XXXX-510-700mA 180996-XXXX-710-880mA 180996-XXXX-890-1050mA	<b>Single Channel</b> CORESM-00350 CORESM-00500 CORESM-00700 CORESM-01050 CORESM-00880  <b>Dual Channel</b> COREDM-00350 COREDM-00500 COREDM-00700 COREDM-01050 COREDM-00880	<b>WL</b> UL "Suitable for Wet Locations" labeled.	

## Housings

Extruded aluminum profile in a 0.080-inch wall thickness. Maximum length of each linear component is 12-ft. .060 aluminum ends are provided where needed at row termini. A one-piece 14GA galvanized steel joiner/aligner bracket is provided for each joint between housings. Internal cold-rolled steel components. Standard or custom hanging points are provided. A custom formulated non-glare matte-white polyester powder coating provides an extremely durable and long lasting finish. Custom color finishes on request.

## Diffusers

Seamless fit diffusers. Flawless and consistent end-to-end fit. Extruded from custom formulated acrylic smooth opal material. Allows maximum light transmission while eliminating pixilation and hot spots. Standard diffuser is 1-2- inch drop style. Optional diffusers; 1-inch or 1-1/2-inch drop style or flat style. Smooth finish compliments the architectural elements.

## LED Modules

High performance linear configured LED module boards. Each board consists of multiple mid-power, high efficacy LEDs in a precise layout eliminating the need for supplemental heat sinking. The boards produce an even and diffuse light which maximizes optical efficiency. Color temperatures available 80 CRI: 3000K, 3500K and 4000K. Upon request: 5000K. Color temperatures available 90 CRI: 2700K, 3000K, 3500K and 4000K.

## Tunable White Option

Field tunable range 2700K through 5700K. 80CRI.

## PoE Drivers

UL 2108 Listed. Plenum Rated. LED output voltage range 12-42VDC. Class 2 rated electrical device. Available in both single channel and dual channel. Efficiency: 92% (typical) at 52VDC input, full load. Constant Current accuracy +/- 3%. Ambient temperature: 0 to 40°C (32 to 104°F). Storage temperature: -40 to 85°C (-40 to 185°F). Max case temperature: 75°C (167°F). Environmental rating: Indoor.

## Dimming Performance- PoE Driver

Dimming: PWM  
Dimming type: Linear  
Dimming frequency: 500Hz  
Dimming range: 1-100%

## Molex- PoE Driver

The Molex CoreSync Programmable Smart LED Driver is a compact low voltage, DC/DC LED driver that can be programmed to specific power outputs, for driving Constant Current LED engines in a wide variety of light fixtures. Controlled, powered and integrated with a Molex CoreSync PoE Gateway. This DC system provides 71.3 usable watts at the powered device, it operates at 52 VDC and has an amperage allowance 1.73 amps. Using this product gives the end user the option of making their building a smart building combining IT and OT to one platform, while being able to control but not limited to cameras, shades, occupancy, traffic patterns and DLH.

## CoreSync Emergency Lighting Bypass

UL 924 Compliant, Indoor Rated. Ambient operating temperature 0-40C (32-104F).

## Electrical- ELB

EM input: 110-277 VAC.  
Output: 12-42 VDC up to 1050MA.  
Standby Power: 1W.

## Operation-ELB

In the event of a power failure, PoE power source failure or disconnection of cabling, the module will bypass normal PoE control and activate the emergency power source. The fixture will power to full brightness and return to normal operation once the emergency has been cleared.

## Corners

Standard 90-degree corners. Custom angled corners.

## Installations

Designed to be suspended on cables. Specify **M**. For direct surface mounting to most ceiling types, specify **M1** and consult factory. For stem mounting specify **M2** and consult factory. Lengths of 12-ft. and less to use one housing with two ends pre-installed. Lengths over 12-ft. will be engineered to job requirements using multiple housings with one end pre-installed at each row end. Lengths over 12-ft. will include appropriate job required quick-connect plug-thru wire harnesses and housing joiners. All individual modules or multiple module runs to include job required feed wire as specified. Standard or custom hanging points will be provided per job specifications.

## Certificate of Safety Compliance and Listings

Luminaire: UL and CUL listed 1598 and bears their label. Suitable for damp locations. Optional: Suitable for wet locations marking is available. Some limitations apply. Contact factory for all details.

## Warranty

5-year limited warranty is standard. Special 10-year warranty available on a job-to-job basis. Complete LED warranty terms available at [www.mercltg.com](http://www.mercltg.com). Actual performance may differ as a result of end-user environment and application. Most LED luminaires are suitable to operate in ambient temperatures from -20C (-4F) to 25C (77F). The following exclusions apply: Luminaires with standby lighting option, integral lighting control options, or wireless control options. Consult factory. LM-79 testing was measured under a controlled 25C (77F) ambient operating temperature.




# MLD2-M PoE Series | LIGHTSTREAMS 2


Architectural Linear LED Illuminating System | Drop or Flat Lens | Suspended or Surface Mount




## Dimensional Data




**Flat Diffuser**



**1/2" Drop**







**1" Drop**



**1-1/2" Drop**


## Mounting Information



## Hanging Accessories

CABLE SETS

STEM SETS



Part #	Description
R5PF-100	Round 5" power feed canopy, Hanging hardware, 100" long 1/16" cable.
R5-100	Round 5" canopy, Hanging hardware, 100" long 1/16" cable.
R2-100	Round 2" canopy, Hanging hardware, 100" long 1/16" cable.
S5PF-100	Square 5" power feed canopy, Hanging hardware, 100" long 1/16" cable.
S5-100	Square 5" canopy, Hanging hardware, 100" long 1/16" cable.
S2-100	Square 2" canopy, Hanging hardware, 100" long 1/16" cable.
RP5-24	Round 5" canopy, Hanging hardware, 24" long 1/2" dia. stem.
SP5-24	Square 5" canopy, Hanging hardware, 24" long 1/2" dia. stem.

Other cable and stem lengths available. Consult factory.

